

2015+ Mustang Windshield Banner

Installation Instructions
P/N: 421903 (R1315-03088)



ROUSH
PERFORMANCE

39555 Schoolcraft Rd, Plymouth MI, 48170 | [800.59.ROUSH](tel:800.59.ROUSH)

2015+ Mustang Windshield Banner

Installation Instructions
P/N: 421903 (R1315-03088)



Application: 2015+ Ford Mustang

2015+ Mustang 5.0L with Automatic/Manual Transmission

2015+ Mustang 3.7L with Automatic/Manual Transmission

2015+ Mustang 2.3L with Automatic/Manual Transmission

Important Note:

Before installing your ROUSH Performance Product, please read the installation manual and verify that all items are present. If you are missing hardware or have any questions, please contact ROUSH Performance at 1-800-59-ROUSH.

TABLE OF CONTENTS

Packing List for 2015+ Mustang Windshield Banner P/N: 421903 (R1315-03088) 3

Equipment and Supplies Required..... 3

Limit of Liability Statement..... 3

Safety Precautions 3

Work Safely! 3

Installation 4

PACKING LIST FOR 2015+ MUSTANG WINDSHIELD BANNER R1315-03088

Description	Part Number	Quantity
"ROUSH" Windshield Banner	1315-03088	1

EQUIPMENT AND SUPPLIES REQUIRED

- Plastic Squeegee
- Masking Tape
- Isopropyl Alcohol and Terry Cloth

If you are missing any items, please call us toll free at 1-800-59-ROUSH.

LIMIT OF LIABILITY STATEMENT

The information contained in this publication was accurate and in effect at the time the publication was approved for printing and is subject to change without notice or liability. ROUSH Performance Products (RPP) reserves the right to revise the information presented herein or to discontinue the production of parts described at any time.

SAFETY PRECAUTIONS

CAREFULLY READ THE IMPORTANT SAFETY PRECAUTIONS and WARNINGS BEFORE PROCEEDING WITH THE INSTALLATION!

Appropriate disassembly, assembly methods and procedures are essential to ensure the personal safety of the individual performing the kit installation. Improper installation due to the failure to correctly follow these instructions could cause personal injury or death. Read each step of the installation manual carefully before starting the installation.

- Always wear safety glasses for eye protection.
- Place ignition switch in the OFF position.
- Always apply the parking brake when working on a vehicle.
- Block the front and rear tire surface to prevent unexpected vehicle movement.
- If working with a lift, always consult vehicle manual for correct lifting specifications.
- Operate the engine only in well-ventilated areas to avoid exposure to carbon monoxide.
- Do not smoke or use flammable items near or around the fuel system.
- Use chemicals and cleaners in well-ventilated areas.
- Batteries produce explosive gases, which can cause personal injury. Therefore, do not allow flames, sparks or flammable substances to come near the battery.
- Keeps hands and any other objects away from the radiator fan blades.
- Keep yourself and your clothing away from moving parts when the engine is running.
- Do not wear loose clothing or jewelry that can get caught in rotating parts or scratch surface finishes.
- Allow the engine, cooling system, brakes and exhaust to cool before working on a vehicle.

WORK SAFELY!

Perform this installation on a good clean level surface for maximum safety and with the engine turned off.

INSTALLATION

The following section will guide you through the installation of the ROUSH windshield banner (R1315-03088).

1. Thoroughly clean the windshield with isopropyl alcohol and a terry cloth to promote strong adhesion of the windshield banner to the windshield.
2. Place the ROUSH windshield banner onto the windshield and align the top edge of the banner with the top edge of the glass. Place a piece of masking tape vertically across the banner near the middle once it is in the correct position in order to hold it in place.



3. Peel off the backing from one edge of the banner up towards the masking tape and trim the backing off as shown below.



4. Pull the portion of the windshield banner that has the backing removed back across the windshield while maintaining constant tension and making sure that it does not contact the glass. Use a plastic squeegee and drag it from the center out to the edge to apply the banner. Once the banner is applied, squeegee out any remaining air bubbles. **Do not squeegee the banner directly across the trimmed edge of the backing.**





5. Peel the protective covering off of the applied portion of the windshield banner up toward the line of masking tape but do not go past the letters that have already been applied. **Do not completely remove the protective covering yet.**



6. Move to the opposite side of the windshield banner, remove the masking tape and remove the rest of the backing. Move the remaining portion of the windshield banner in place while keeping constant tension and making sure that it does not contact the glass. Use a plastic squeegee and drag it from the center out to the edge to apply the banner. Once the banner is applied, squeegee out any remaining air bubbles.



7. Continue removing the protective covering from the rest of the windshield banner. Using a plastic squeegee, carefully remove any remaining air bubbles.



8. Allow several hours of dry time before cleaning. Never power wash or scrape your ROUSH windshield banner.

